

# Stanilite **PREMIUM**

PRODUCT RANGE

## Saturn Circular Emergency

- Superior Photometric Performance
- Hi Temperature NiMH Batteries
- Premium Circular Emergency Luminaire
- 28W 2D or 32W Compact Lamp Options
- Standard or Computer Monitored Options

The Stanilite "Saturn" range of Emergency fittings have been designed to deliver the efficiency and reliability of Stanilite's Premium "Linear" emergency batten range into a more architecturally pleasing "Circular" Emergency fitting. Saturn emergency fittings are suitable for wall or ceiling installation in many commercial applications including office areas, foyers and stairwell areas.

The Superior photometric performance of the "Saturn" range gives higher light output per unit meaning fewer fittings need to be installed in a given area, reducing installation, maintenance and running costs.

All Saturn emergency fittings are available in either Standard (non-monitored) or Nexus (computer monitored) versions and have new technology Hi-Temp rated Nickel Metal Hydride (NiMH) batteries as standard.

Saturn fittings use high quality white powder coated, zinc steel bases with tough Opal Acrylic domed diffusers. Surface mount electronics as well as 105 deg C rated electronic components give market leading service life and reliability. All Stanilite Saturn fittings are tested to comply with AS/NZS 4051 EMC Standard and AS/NZS 2293 Evacuation Lighting Standard.

Due to ongoing product development, specification changes may result

## Ordering Information & Photometrics

Part Number	Description	Classification	Ceiling Mount	Wall Mount
SA128M2D	Stanilite Premium Saturn Circular 1 x 28W 2D Maintained Emergency	C0 C90	D25 D25	D12.5 D10
SA132M	Stanilite Premium Saturn Circular 1 x 32W Maintained Emergency	C0 C90	D20 D20	
SANXS128M2D	Stanilite Premium Saturn Circular Nexus Computer Monitored 1 x 28W 2D Maintained Emergency	C0 C90	D25 D25	B5 D10
SANXS132M	Stanilite Premium Saturn Circular Nexus Computer Monitored 1 x 32W Maintained Emergency	C0 C90	D20 D20	

**Notes:** The code NXS in any part number denotes Nexus Emergency Monitoring is provided.  
Lamps are included in 28 & 32-Watt fittings.

## Luminaire Spacings

Classification	Mounting Height in Metres							
	2.1	2.4	2.7	3	3.6	4	5	6
B5	4.7	4.9	5.1	5.3	5.4	5.4	5.1	4.1
D10	10.2	10.6	10.9	11.1	11.4	11.5	11.6	11.2
D12.5	11.1	11.5	11.8	12.1	12.5	12.7	13	12.8
D20	13.1	13.6	14.1	14.5	15.1	15.5	16.1	16.4
D25	14.2	14.7	15.3	15.7	16.5	16.9	17.7	18.1

## Dimensions

Model	Weight Kg	Diameter D	Base H BH.	Height H
SA**128M2D	3.0	370mm	50mm	138mm
SA**132M	3.0	370mm	50mm	138mm

**For more information on Stanilite Products**

**Phone 1300 666 595**

**Fax 1300 666 594**

**www.tnbaust.com**

Thomas & Betts Australasia Pty Ltd  
Head Office 23a Nyrang St Lidcombe NSW 2141  
ABN 62 074 810 898

**Thomas & Betts**  
*Leading the Way*