

Stanilite PREMIUM

PRODUCT RANGE




Made in Australia

18W Quickfit™ Exit range

- Premium 18W Exit Standard & Jumbo sizes
- Quickfit Slide Connect Bracket
- Universal Wall or Ceiling mount
- Hi Temperature NiMH Batteries
- Standard or Computer Monitored Options

The Stanilite Quickfit 18W Exit range provides a Premium Quality Exit for use in many Commercial and Industrial applications where conventional sized Exit's do not provide adequate coverage. The Stanilite 18W Quickfit is available in Standard 100mm and Jumbo 150mm pictogram sizes providing viewing distances up to 36 metres (ref. AS/NZS2293).








The 18W Quickfit uses a powder coated steel slide connect bracket, similar but larger to that used with the 10W Quickfit range. The design of the 18W Quickfit and its bracket enables it to be installed on the wall or ceiling with the same diffusers. The power socket in the bracket uses large 16mm power terminals enabling TPS junctioning at the bracket, all covered by a full-length protective mains cover.

All fittings are available in either non-monitored or Nexus computer monitored versions and have new technology Hi-Temp rated Nickel Metal Hydride (NiMH) batteries as standard.

Stanilite 18W Quickfits use ABS/Extruded Aluminium bodies with high quality Opal Acrylic domed diffusers. Surface mount electronics as well as 105 deg C rated electronic components give market leading service life and reliability. All Stanilite 18W Quickfits are tested to comply with AS/NZS 4051 EMC Standard and AS/NZS 2293 Evacuation Lighting Standard.

Due to ongoing product development, specification changes may result

QF (NXS) 218S Standard Exit Diffuser Options (Silk Screened)

Single Sided		Double Sided	
	0001 (31-QL1)		005
	0002 (31-QL2)		006
	0003 (31-QL3)		007
	0004 (31-QL4)		

Note: Part Number for single diffuser shown in brackets.

QFJ (NXS) 218S Jumbo Exit Diffuser Options (Peel Off Arrow)

Single Sided		Double Sided	
	0001 (31-QJ1)		005

Note: Part Number for single diffuser shown in brackets. Peel Off arrow diffusers can be configured to any option as per QF218S

Ordering Information & Photometrics

Body Part No.	Description
QF218SQL-000*	Stanilite Quickfit Exit 2 x 18W Sustained, 24-metre maximum viewing distance
QFNXS218SQL-000*	Stanilite Quickfit Exit 2 x 18W Sustained, Nexus Monitored 24-metre maximum viewing distance
QFJ218SQJ-000*	Stanilite Jumbo Quickfit Exit 2 x 18W Sustained, 36-metre maximum viewing distance
QFJNXS218SQJ-000*	Stanilite Jumbo Quickfit Exit 2 x 18W Sustained, Nexus Monitored Peel Off Arrow Diffuser 36-metre maximum viewing distance

Notes: The code NXS in any part number denotes Nexus Emergency Monitoring is provided.

Dimensions

Model	Weight Kg	Length L	Width Single Sided	Width Double Sided	Height H
QF**218S	4.0	634mm	87mm	102mm	218mm
QFJ**218S	5.0	634mm	87mm	102mm	293mm

For more information on Stanilite Products

Phone 1300 666 595

Fax 1300 666 594

www.tnbaust.com

Thomas & Betts Australasia Pty Ltd
 Head Office 23a Nyrang St Lidcombe NSW 2141
 ABN 62 074 810 898

Thomas & Betts
Leading the Way